

SCHEDULE-III					
EXTERIOR PAINTING AND WINDOW REPLACEMENT WORK					
Item No.	Items	Quantity	Unit	Rate	Amount
A Building Exterior - Demolition \ Removing					
1	Removing doors and Windows with frames and stacking the materials directed with all leads, lifts etc. complete all as directed by Bank's Engineer /Architect.	25.00	Sqm		
				Total of A	
B Building Exterior modification - Construction					
1	Providing and applying two or more coats of exterior acrylic emulsion paint (APEX)confirming to corresponding I.S. of approved manufacture and of approved colour to the plastered surfaces including cleaning, removing shrubs, plants, algae, fungal growth, on existing surfaces, preparing the plaster surface, applying primer coat ,including scaffolding etc complete. (For External Walls)	2,152.00	Sqm		
2	Providing and fixing in position (as per 1868 / 1982) Aluminum sliding window of three tracks with standard rectangular pipe with window frame bottom track section 92 x31.75 x 1.30 mm at weight 1.070 kg/Rmt.. Top and side track section 92 x 31.75 x 1.30 mm at weight 0.933 kg/Rmt. The shutter should be of bearing bottom 40 x 18 x 1.25 mm at weight 0.417 kg/Rmt. Inter locking section 40 x 18 x 1.10 mm at weight 0.469 kg/Rmt. and handle and top section 40 x 18 x 1.25 mm at weight 0.417 kg/Rmt. As per detailed drawings and as directed by Engineerincharge with all necessary Aluminum sections fixtures and fastenings such as roller bearing in nylon casting and self locking catch fitted in vertical section of shutter including 5 mm thick plain glass and aluminum mosquito net shutter with stainless steel jail with all required screws and nuts etc, complete. With powder coated as per approved colour.	11.00	Sqm		
3	Providing and fixing in position. (as per I.S.1868 / 1982) Aluminium sliding window of two tracks powder coated as per approved colour.with rectangular pipe having standard size And window frame bottom track section 61.85 x 31.75 x 1.20 mm at weight 0.695 kg/Rmt. Top and side track section 61.85 x 31.75 x 1.30 mm at weight 0.659 kg/Rmt. The shutter should be of bearing bottom 40 x 18 x 1.25 mm at weight 0.417 kg/Rmt. Inter locking section 40 x18 x 1.10 mm at weight 0.469 kg/Rmt. And handle section 40 x 18 x 1.25 mm at weight 0.417 kg/Rmt. and top section 40 x 18 x 1.25 mm at weight 0.417 kg/Rmt. As per detailed drawings and as directed by Engineer in charge with all necessary Aluminum sections fixtures and fastenings such as roller bearing in nylon casting and self locking catch fitted in vertical section of shutter including 5 mm thick plain glass with all required screws and nuts etc, complete.	70.00	Sqm		
				Total of B	

Item No.	Items	Quantity	Unit	Rate	Amount

SUMMARY

DESCRIPTION	AMOUNT(RS)
TOTAL A	
TOTAL B	
GROSS TOTAL	
ADD GST()	
GRAND TOTAL OF SCHEDULE-III	

Amount in Words: _____

Signature of Contractor:

Stamp:

Date: